

## Technical Specifications

### Mechanical

<b>Dimensions</b>	141.8 x 127.6 x 30 mm (5.6 x 5 x 1.2")
<b>Weight</b>	520 g (1.1 lb)
<b>Enclosure material</b>	Polycarbonate
<b>Resistance</b>	IK04

### Hardware

<b>Processor</b>	Quad-core ARM® Cortex®-A53 at 1.5 GHz
<b>Memory information</b>	2 GB DDR4
<b>Management interface</b>	Ethernet Bluetooth
<b>Networking interface</b>	LAN: (4) 2.5 GbE RJ45 ports  WAN: (1) 2.5 GbE RJ45 port
<b>Power method</b>	USB type C (5V/3A)
<b>Supported voltage range</b>	100–240V
<b>Max. power consumption</b>	9.6W
<b>LED</b>	Ethernet White: link/activity
<b>Button</b>	(1) Factory reset
<b>Ambient operating temperature</b>	-10 to 40° C (14 to 104° F)
<b>Ambient operating humidity</b>	5 to 95% noncondensing
<b>Certifications</b>	CE, FCC, IC

### Gateway Features

<b>Performance</b>	WiFi QoS with UniFi APs Application, domain, and country-based QoS Application and device type identification Internet quality and outage reporting
<b>Next-generation security</b>	Application-aware firewall rules Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation Full stateful firewall
<b>Advanced networking</b>	License-free SD-WAN* WireGuard, L2TP and OpenVPN server OpenVPN client OpenVPN and IPsec site-to-site VPN One-click Teleport* and Identity Enterprise VPN** Policy-based WAN and VPN routing DHCP relay Customizable DHCP server IPv6 ISP support

\*When paired with a Cloud Key or Official UniFi Hosting.

\*\*When paired with a Cloud Key.

## Application Requirements

UniFi Network

Version 8.1.113 and later